NSN 5970-01-432-6466

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-432-6466

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 200.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

Any acceptable as supplied

Distance From Centerline Of Small End To Edge Of Large End:

Any acceptable as supplied

Main Body Small End Inside Diameter:

0.580 inches as supplied

Main Body Large End Inside Diameter:

1.120 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

Any acceptable as supplied

Angle Between Large End And Small End Centerlines In Deg:

90.0 as supplied

Min. Tensile Strength (psi):

1800 pounds per square inch

Special Features:

Yellow color stripe; large end has lip

Flexibility:

Flexible

Height:

1.070 inches after unrestricted recovery

Color:

Black

Material:

Plastic, fluoroelastomer, mil-i-81765/4

Material:

Plastic, fluoroelastomer, mil-i-81765/4

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-432-6466

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A22500