NSN 5970-01-433-5585

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-433-5585

Reliability Indicator:

Not established

Tempurature Rating:

-70.0 degrees celsius and 150.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant

Distance From Centerline Of Main Body To End Of First Branch:

2.370 inches after unrestricted recovery

Main Body Inside Diameter:

1.290 inches as supplied

First Branch Inside Diameter:

0.840 inches as supplied

Main Body Wall Thickness:

0.050 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Main Bodylength:

4.740 inches after unrestricted recovery

Min. Tensile Strength (psi):

2200 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Rubber, synthetic, viton polymer blend, rt-1313, raychem corp.

Material:

Rubber, synthetic, viton polymer blend, rt-1313, raychem corp.

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500