Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-433-5585

Reliability Indicator: Not established **Tempurature Rating:** -70.0 degrees celsius and 150.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter: 1.290 inches as supplied First Branch Inside Diameter: 0.840 inches as supplied Main Body Wall Thickness: 0.050 inches after unrestricted recovery **First Branch Wall Thickness:** 0.050 inches after unrestricted recovery Main Bodylength: 4.740 inches after unrestricted recovery Min. Tensile Strength (psi): 2200 pounds per square inch **Special Features:** Inside adhesive coated Flexibility: Flexible Color: Black Material: Rubber, synthetic, viton polymer blend, rt-1313, raychem corp. Material: Rubber, synthetic, viton polymer blend, rt-1313, raychem corp. Style Designator: Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500