## NSN 5970-01-433-5588

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-433-5588 **Reliability Indicator:** 

Not established

**Tempurature Rating:** 

-70.0 degrees celsius and 150.0 degrees celsius

**Environmental Protection:** 

Flame resistant and mildew resistant

Distance From Centerline Of Main Body To End Of First Branch:

1.590 inches after unrestricted recovery

Main Body Inside Diameter:

0.720 inches as supplied

**First Branch Inside Diameter:** 

0.460 inches as supplied

Main Body Wall Thickness:

0.040 inches after unrestricted recovery

**First Branch Wall Thickness:** 

0.040 inches after unrestricted recovery

Main Bodylength:

3.180 inches after unrestricted recovery

Min. Tensile Strength (psi):

2200 pounds per square inch

**Special Features:** 

Inside adhesive coated

Flexibility:

Flexible Color:

Black

Material:

Rubber, synthetic, viton polymer blend, rt-1313, raychem corp

Material:

Rubber, synthetic, viton polymer blend, rt-1313, raychem corp

**Style Designator:** 

Transition-t

**Dielectric Material Voltage Rating Per Unit Thickness:** 

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A22500