NSN 5970-01-434-6534

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-434-6534 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant **Main Body Wall Thickness:** 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery **End Application:** Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Plastic, elastomeric polymer blend, rt-1321, raychem corp **Style Designator:** Boot-straight **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5970-01-434-6534

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500