

View Online at https://aerobasegroup.com/nsn/5970-01-434-6534

Reliability Indicator: Not estabilished Tempurature Rating: -55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brack Prom Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brack Prom Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brack Prom Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brack Prom Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brack Prom Top Of Shoulder To Small End Of Main Body: 1.000 pounds per square inch	
Tempurature Rating: -55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Dof Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brad Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material	Reliability Indicator:
-5.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches a supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Dof Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Brad Application: Mrap - cougar cat1 a1 Min Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Plexibile Distance from polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per	Not established
Environmental Protection: Flame resistant and mildew resistant Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Bitan Cougar cat1 a1 Min Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Mate	Tempurature Rating:
Flame resistant and mildiew resistant Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Min Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside achesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material:	-55.0 degrees celsius
Main Body Wall Thickness: 0.090 inches after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar catl a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 20.0.0 volts per military /0.001 inch/ Sheft Life: Na	Environmental Protection:
0.990 incles after unrestricted recovery Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar catl a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside achesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Bot-straight Dielectric Material Voltage Rating Per Unit Thickness: 20.0 volts per military /0.001 inch/ Sheff Life: Na	Flame resistant and mildew resistant
Main Bodylength: 2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 20.0.0 volts per military /0.001 inch/ Sheff Life: Na	Main Body Wall Thickness:
2.100 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Sheff Life: Na	0.090 inches after unrestricted recovery
Main Body Small End Inside Diameter: 0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexibile Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Sheft Life: N/a	Main Bodylength:
0.380 inches as supplied Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	2.100 inches after unrestricted recovery
Main Body Large End Inside Diameter: 1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Miterial: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 20.0 volts per military /0.001 inch/ Sheff Life: N/a	Main Body Small End Inside Diameter:
1.010 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	0.380 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:1.100 inches after unrestricted recoveryDistance From Top Of Shoulder To Small End Of Main Body:0.620 inches after unrestricted recoveryEnd Application:Mrap - cougar cat1 a1Min. Tensile Strength (psi):1500 pounds per square inchSpecial Features:Inside adhesive coatedFlexibility:PlexibleColor:BlackMaterial:Plastic, elastomeric polymer blend, rt-1321, raychem corpMaterial:Plastic, elastomeric polymer blend, rt-1321, raychem corpSyle Designator:Boot-straightDielectric Material Voltage Rating Per Unit Thickness:200.0 volts per military /0.001 inch/Sheff Life:N/a	Main Body Large End Inside Diameter:
1.100 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	1.010 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Distance From Bottom Of Shoulder To Large End Of Main Body:
0.620 inches after unrestricted recovery End Application: Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	1.100 inches after unrestricted recovery
End Application:Mrap - cougar cat1 a1Min. Tensile Strength (psi):1500 pounds per square inchSpecial Features:Inside adhesive coatedFlexibility:FlexibleColor:BlackMaterial:Plastic, elastomeric polymer blend, rt-1321, raychem corpMaterial:Plastic, elastomeric polymer blend, rt-1321, raychem corpStyle Designator:Boot-straightDielectric Material Voltage Rating Per Unit Thickness:200.0 volts per military /0.001 inch/Shelf Life:N/a	Distance From Top Of Shoulder To Small End Of Main Body:
Mrap - cougar cat1 a1 Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexibile Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	0.620 inches after unrestricted recovery
Min. Tensile Strength (psi): 1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	End Application:
1500 pounds per square inch Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Mrap - cougar cat1 a1
Special Features: Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Min. Tensile Strength (psi):
Inside adhesive coated Flexibility: Flexibile Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	1500 pounds per square inch
Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Special Features:
Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Inside adhesive coated
Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Flexibility:
Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Flexible
Material:Plastic, elastomeric polymer blend, rt-1321, raychem corpMaterial:Plastic, elastomeric polymer blend, rt-1321, raychem corpStyle Designator:Boot-straightDielectric Material Voltage Rating Per Unit Thickness:200.0 volts per military /0.001 inch/Shelf Life:N/a	Color:
Plastic, elastomeric polymer blend, rt-1321, raychem corp Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Black
Material: Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Material:
Plastic, elastomeric polymer blend, rt-1321, raychem corp Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Plastic, elastomeric polymer blend, rt-1321, raychem corp
Style Designator: Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Material:
Boot-straight Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Plastic, elastomeric polymer blend, rt-1321, raychem corp
Dielectric Material Voltage Rating Per Unit Thickness: 200.0 volts per military /0.001 inch/ Shelf Life: N/a	Style Designator:
200.0 volts per military /0.001 inch/ Shelf Life: N/a	Boot-straight
Shelf Life: N/a	Dielectric Material Voltage Rating Per Unit Thickness:
N/a	200.0 volts per military /0.001 inch/
	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No

NSN 5970-01-434-6534

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

