NSN 5970-01-435-3006

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-435-3006

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius and 225.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Main Body Wall Thickness: 0.150 inches after unrestricted recovery Main Bodylength: 3.850 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.750 inches as supplied Main Body Large End Inside Diameter: 1.490 inches as supplied Distance From Bottom Of Shoulder To Large End Of Main Body: 2.350 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Small end wall thk. Tapers to 0.080 in.; includes molding ports Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Boot-straight **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A22500