NSN 5970-01-435-3637

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-435-3637

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Large End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

1.750 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.190 inches as supplied

Main Body Large End Inside Diameter:

0.700 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

0.860 inches after unrestricted recovery

End Largest Diameter:

0.630 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Special Features:

Inside adhesive coated; large end inside diameter has lip

Flexibility:

Flexible

Height:

0.640 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-1304, raychem corp.

Material:

Plastic, polyolefin, rt-1304, raychem corp.

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

NSN 5970-01-435-3637

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A22500