Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-437-4790

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Flame resistant and mildew resistant and solvent resistant and water resistant
Large End Wall Thickness Of Main Body:
0.070 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.045 inches after unrestricted recovery
Main Bodylength:
3.500 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.720 inches as supplied
Main Body Large End Inside Diameter:
1.160 inches as supplied
End Largest Diameter:
0.880 inches after unrestricted recovery
Min. Tensile Strength (psi):
1800 pounds per square inch
Lip Height:
0.120 inches after unrestricted recovery
Lip Width:
0.040 inches after unrestricted recovery
Flexibility:
Flexible
Height:
0.820 inches after unrestricted recovery
Color:
Black
Material:
Rubber, viton, rt-1312, raychem corp.
Material:
Rubber, viton, rt-1312, raychem corp.
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5970-01-437-4790

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500