NSN 5970-01-442-1777

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-442-1777

| View Online at https://aerobasegroup.com/nsn/5970-01-442-1777 |
|--|
| Reliability Indicator: |
| Not established |
| Tempurature Rating: |
| -55.0 degrees celsius and 225.0 degrees celsius |
| Environmental Protection: |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant |
| Main Body Wall Thickness: |
| 0.150 inches after unrestricted recovery |
| Main Bodylength: |
| 6.350 inches after unrestricted recovery |
| Main Body Small End Inside Diameter: |
| 2.540 inches as supplied |
| Main Body Large End Inside Diameter: |
| 2.540 inches as supplied |
| Distance From Bottom Of Shoulder To Large End Of Main Body: |
| 3.550 inches after unrestricted recovery |
| Distance From Top Of Shoulder To Small End Of Main Body: |
| 1.880 inches after unrestricted recovery |
| Min. Tensile Strength (psi): |
| 1500 pounds per square inch |
| Special Features: |
| Includes molding ports; inside adhesive coated |
| Flexibility: |
| Semirigid |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin, rt-301, raychem corp |
| Material: |
| Plastic, polyolefin, rt-301, raychem corp |
| Style Designator: |
| Boot-straight |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 200.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A22500