

View Online at <https://aerobasegroup.com/nsn/5970-01-447-4438>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant and crack resistant

**Expanded Inside Diameter:**

19.0 millimeters and 0.750 inches

**Recovered Inside Diameter:**

9.5 millimeters and 0.375 inches

**Recovered Wall Thickness:**

Between 0.7 millimeters and 0.027 inches and 0.033 inches

**Heat Shrinkage Rating In Percent:**

50.0

**End Application:**

Jet1-shore ba

**Design Form:**

Full round

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Product Name:**

Single wall tubing: flexible, flame-retardant, general purpose, polyolefin tubing

**Flexibility:**

Flexible

**Color:**

Clear

**Material:**

Plastic, polyolefin, mil-i-23053/5, class 1

**Material:**

Plastic cross-linked polyolefin

**Style Designator:**

Shrinkable

**Dielectric Material Voltage Rating Per Unit Thickness:**

500.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500