Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-447-4438

view Online at https://aerobasegroup.com/hsi//39/0-01-44/-4436	
Reliability Indicator:	
Not established	
Tempurature Rating:	
-55.0 degrees celsius and 135.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and water resistant and crack resistant	
Expanded Inside Diameter:	
19.0 millimeters and 0.750 inches	
Recovered Inside Diameter:	
9.5 millimeters and 0.375 inches	
Recovered Wall Thickness:	
Between 0.7 millimeters and 0.027 inches and 0.033 inches	
Heat Shrinkage Rating In Percent:	
50.0	
End Application:	
Jet1-shore ba	
Design Form:	
Full round	
Min. Tensile Strength (psi):	
1500 pounds per square inch	
Product Name:	
Single wall tubing: flexible, flame-retardant, general purpose, polyolefin tubing	
Flexibility:	
Flexible	
Color:	
Clear	
Material:	
Plastic, polyolefin, mil-i-23053/5, class 1	
Material:	
Plastic cross-linked polyolefin	
Style Designator:	
Shrinkable	
Dielectric Material Voltage Rating Per Unit Thickness:	
500.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A22500	