NSN 5970-01-465-4198

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-465-4198

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Petroleum resistant

Large End Wall Thickness Of Main Body:

0.080 inches as supplied

Small End Wall Thickness Of Main Body:

0.045 inches as supplied

Main Bodylength:

8.410 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.720 inches as supplied

Main Body Large End Inside Diameter:

1.720 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

6.660 inches after unrestricted recovery

End Largest Diameter:

1.440 inches after unrestricted recovery

Min. Tensile Strength (psi):

1800 pounds per square inch

Special Features:

Color stripe and drain added; inside is adhesive coated

Flexibility:

Flexible

Height:

1.080 inches after unrestricted recovery

Color:

Black

Material:

Plastic polyoelfin, mil-i-81765/1 type 2 or plastic polyoelfin, raychem rt-1304

Material:

Plastic polyoelfin, mil-i-81765/1 type 2 or plastic polyoelfin, raychem rt-1304

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

350.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-465-4198

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



			on:	

No

Fiig:

A22500