## NSN 5970-01-478-5204

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-478-5204 **Reliability Indicator:** Established **Tempurature Rating:** -55.0 degrees celsius and 135.0 degrees celsius **Main Body Inside Diameter:** 1.520 inches as supplied First Branch Inside Diameter: 0.760 inches as supplied **Second Branch Inside Diameter:** 0.760 inches as supplied **Third Branch Inside Diameter:** 0.760 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** Any acceptable Main Body Wall Thickness: 0.120 inches after unrestricted recovery First Branch Wall Thickness: 0.070 inches after unrestricted recovery **Second Branch Wall Thickness:** 0.070 inches after unrestricted recovery **Third Branch Wall Thickness:** 0.070 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 2.650 inches after unrestricted recovery Main Bodylength: 5.320 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: Any acceptable **Special Features:** Adhesive part number s-1017 or s-1048 Flexibility: Semirigid Color: Black Material: Plastic, polyolefin Material:

Shelf Life:

Plastic polyolefin

Style Designator:

Transition-1 to 3 cables

N/a

## NSN 5970-01-478-5204

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



		• -					
ш	ın	18 1	r 1+	Me	20	ıır	Δ.
u	,,,	IL	v.	IAIC	as	uı	┖.

--

Demilitarization:

No

Fiig:

A22500