Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-478-5204

Reliability Indicator:
Established
Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Main Body Inside Diameter:
1.520 inches as supplied
First Branch Inside Diameter:
0.760 inches as supplied
Second Branch Inside Diameter:
0.760 inches as supplied
Third Branch Inside Diameter:
0.760 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
Any acceptable
Main Body Wall Thickness:
0.120 inches after unrestricted recovery
First Branch Wall Thickness:
0.070 inches after unrestricted recovery
Second Branch Wall Thickness:
0.070 inches after unrestricted recovery
Third Branch Wall Thickness:
0.070 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
2.650 inches after unrestricted recovery
Main Bodylength:
5.320 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
Any acceptable
Special Features:
Adhesive part number s-1017 or s-1048
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin
Material:
Plastic polyolefin
Style Designator:
Transition-1 to 3 cables
Shelf Life:
N/a

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A22500