# NSN 5970-01-484-0959

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-484-0959

#### **Environmental Protection:**

Mildew resistant

#### **Main Body Inside Diameter:**

0.490 inches after unrestricted recovery and 1.060 inches after unrestricted recovery

#### First Branch Inside Diameter:

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

#### **Second Branch Inside Diameter:**

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

#### Third Branch Inside Diameter:

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

#### **Fourth Branch Inside Diameter:**

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

#### Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

1.746 inches after unrestricted recovery and 2.134 inches after unrestricted recovery

#### Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.593 inches after unrestricted recovery and 1.947 inches after unrestricted recovery

#### **Distance From Edge Of Main Body To Intersecting Centerlines:**

1.836 inches after unrestricted recovery and 2.244 inches after unrestricted recovery

#### Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

## Angle Between Main Body And Second Branch Centerlines In Deg:

15.0 after unrestricted recovery

#### Min. Tensile Strength (psi):

1500 pounds per square inch

#### **Product Name:**

Transition, 4 finger

# Flexibility:

Flexible

Color: Black

#### Material:

Plastic, polyolefin

### Material:

Plastic polyolefin

# **Style Designator:**

Transition-1 to 4 cables

#### Shelf Life:

N/a

# **Unit Of Measure:**

#### **Demilitarization:**

No

# NSN 5970-01-484-0959

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500