NSN 5970-01-484-0959

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-484-0959

Environmental Protection:

Mildew resistant

Main Body Inside Diameter:

0.490 inches after unrestricted recovery and 1.060 inches after unrestricted recovery

First Branch Inside Diameter:

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

Second Branch Inside Diameter:

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

Third Branch Inside Diameter:

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

Fourth Branch Inside Diameter:

0.240 inches after unrestricted recovery and 0.520 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

1.746 inches after unrestricted recovery and 2.134 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.593 inches after unrestricted recovery and 1.947 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.836 inches after unrestricted recovery and 2.244 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

15.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Product Name:

Transition, 4 finger

Flexibility:

Flexible

Color: Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Transition-1 to 4 cables

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5970-01-484-0959

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500