## NSN 5970-01-494-2847

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-494-2847

**Reliability Indicator:** 

Not established

**Main Body Inside Diameter:** 

0.760 inches as supplied

First Branch Inside Diameter:

0.520 inches as supplied

**Second Branch Inside Diameter:** 

0.520 inches as supplied

Third Branch Inside Diameter:

0.520 inches as supplied

**Fourth Branch Inside Diameter:** 

0.520 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

1.940 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.770 inches after unrestricted recovery

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

**Second Branch Wall Thickness:** 

0.060 inches after unrestricted recovery

**Third Branch Wall Thickness:** 

0.060 inches after unrestricted recovery

**Fourth Branch Wall Thickness:** 

0.060 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:** 

1.420 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

15.0 after unrestricted recovery

**Special Features:** 

Adhesive coating, s-1017; s-1048

Flexibility:

Not specified

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

## NSN 5970-01-494-2847

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Styl	۹	D	26	ini	na	t٥	r·
Oty:		_	-3	יפי	IIG	w	٠.

Transition-1 to 4 cables

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A22500