## NSN 5970-01-514-2448

No Fiig: A22500

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-514-2448 **Reliability Indicator:** Not established **Tempurature Rating:** -75.0 degrees celsius and 150.0 degrees celsius **Main Body Inside Diameter:** 1.570 inches as supplied First Branch Inside Diameter: 0.910 inches as supplied **Second Branch Inside Diameter:** 0.910 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 3.230 inches after unrestricted recovery Main Body Wall Thickness: 0.096 inches after unrestricted recovery and 0.144 inches after unrestricted recovery First Branch Wall Thickness: 0.080 inches after unrestricted recovery and 0.120 inches after unrestricted recovery **Second Branch Wall Thickness:** 0.080 inches after unrestricted recovery and 0.120 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 2.600 inches after unrestricted recovery Angle Between Main Body And Second Branch Centerlines In Deg: 16.6 after unrestricted recovery and 18.4 after unrestricted recovery **Special Features:** Heat recoverable screen, mat'l is fluid-resistant modified elastomer; agavg1005-01-319-2649; wsd: helicopter observation (ahip), oh-58d Flexibility: Rigid Color: Black Style Designator: Transition-y Shelf Life: N/a **Unit Of Measure: Demilitarization:**