Special Purpose Electrical Insulation Sleeving - Page 1 of 1



oh-58d

View Online at https://aerobasegroup.com/nsn/5970-01-514-2448

Reliability Indicator:	
Not established	
Tempurature Rating:	
-75.0 degrees celsius and 150.0 degrees celsius	
Main Body Inside Diameter:	
1.570 inches as supplied	
First Branch Inside Diameter:	
0.910 inches as supplied	
Second Branch Inside Diameter:	
0.910 inches as supplied	
Distance From Intersecting Centerline Of Main Body To End Of First Branch:	
3.230 inches after unrestricted recovery	
Main Body Wall Thickness:	
0.096 inches after unrestricted recovery and 0.144 inches after unrestricted recovery	
First Branch Wall Thickness:	
0.080 inches after unrestricted recovery and 0.120 inches after unrestricted recovery	
Second Branch Wall Thickness:	
0.080 inches after unrestricted recovery and 0.120 inches after unrestricted recovery	
Distance From Edge Of Main Body To Intersecting Centerlines:	
2.600 inches after unrestricted recovery	
Angle Between Main Body And Second Branch Centerlines In Deg:	
16.6 after unrestricted recovery and 18.4 after unrestricted recovery	
Special Features:	
Heat recoverable screen, mat'l is fluid-resistant modified elastomer; agavg1005-01-319-2649;	wsd: helicopter observation (ahip),
Flexibility:	
Rigid	
Color:	
Black	
Style Designator:	
Transition-y	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A22500	