NSN 5970-01-522-8184

Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-522-8184

Reliability Indicator:

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius and 110.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant and corrosion resistant and water resistant **Expanded Inside Diameter:** 0.355 inches **Recovered Inside Diameter:** 0.187 inches **Recovered Wall Thickness:** Between 0.024 inches and 0.034 inches **Heat Shrinkage Rating In Percent:** 50.0 **Design Form:** Full round **Features Provided:** Adhesive coating Min. Tensile Strength (psi): 1800 pounds per square inch **Product Name:** Tubing, polyolefin, dual wall (with adhesive), heat shrinkable Flexibility: Flexible Color: Black Material: Plastic, polyolefin, mil-i-23053/5 **Style Designator:** Shrinkable **Dielectric Material Voltage Rating Per Unit Thickness:** 800.0 volts per military /0.001 inch/ **Specification Data:** 813349-mil-i-23053/4/superseded government specification **Specification Or Standard:** 2 class and 202 size and 0 color Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5970-01-522-8184

Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500