Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-522-8208

Reliability Indicator: Not established Tempurature Rating:

-55.0 degrees celsius and 110.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and corrosion resistant and water resistant

Expanded Inside Diameter:

0.475 inches

Recovered Inside Diameter:

0.250 inches

Recovered Wall Thickness:

Between 0.025 inches and 0.035 inches

Heat Shrinkage Rating In Percent:

50.0

Design Form:

Full round

Features Provided:

Adhesive coating

Min. Tensile Strength (psi):

1800 pounds per square inch

Product Name:

Tubing, polyolefin, dual wall (with adhesive), heat shrinkable

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, mil-i-23053/5

Style Designator:

Shrinkable

Dielectric Material Voltage Rating Per Unit Thickness:

800.0 volts per military /0.001 inch/

Specification Data:

81349-mil-i-23053/4/superseded government specification

Specification Or Standard:

2 class and 203 size and 0 color

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Electrical Insulation Sleeving - Page 2 of 2



Fiig: A22500

Mil-std (military Standard):

Mil-i-23053 spec.