

View Online at <https://aerobasegroup.com/nsn/5970-01-526-1973>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 120.0 degrees celsius

Environmental Protection:

Corrosion resistant and mildew resistant and water resistant

Main Body Inside Diameter:

1.060 inches as supplied

First Branch Inside Diameter:

0.260 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.410 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.040 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.620 inches after unrestricted recovery

Main Bodylength:

3.640 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

End Application:

An/wld- (v) mine hunting sys; fwd elect sec

Features Provided:

Adhesive coating

Product Name:

Heat shrinkable molded transition, 45 degree

Special Features:

Adhesive code 86 - high performance pre-coat

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Transition-45 degrees

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500