

View Online at <https://aerobasegroup.com/nsn/5970-01-527-3786>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 110.0 degrees celsius

Environmental Protection:

Corrosion resistant and mildew resistant and water resistant

Expanded Inside Diameter:

0.475 inches

Recovered Inside Diameter:

0.250 inches

Recovered Wall Thickness:

Between 0.025 inches and 0.035 inches

Heat Shrinkage Rating In Percent:

47.4

End Application:

An/wld- (v) mine hunting system; fuel/elect. Assembly

Design Form:

Full round

Min. Tensile Strength (psi):

1500 pounds per square inch

Product Name:

Insulation sleeving, electrical, heat shrinkable, polyolefin, dual-wall crosslinked

Special Features:

Melttable inner wall 0.005 in. Thk

Flexibility:

Flexible

Color:

Yellow

Material:

Plastic, polyolefin, mil-i-23053/4, class 2

Material:

Plastic polyolefin

Style Designator:

Shrinkable

Dielectric Material Voltage Rating Per Unit Thickness:

500.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500