## NSN 5970-01-527-6268

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-527-6268

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Inside Diameter:
2.190 inches as supplied
First Branch Inside Diameter:
1.060 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
3.760 inches as supplied
Main Body Wall Thickness:
0.100 inches as supplied
First Branch Wall Thickness:
0.100 inches as supplied
Distance From Edge Of Main Body To Intersecting Centerlines:
3.760 inches as supplied
Main Bodylength:
7.990 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
45.0 as supplied
End Application:
An/wld- (v) mine hunting system
Min. Tensile Strength (psi):
1500 pounds per square inch
Special Features:
Inside adhesive coated
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Transition-45 degrees
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5970-01-527-6268

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500