

View Online at <https://aerobasegroup.com/nsn/5970-01-527-8814>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius and 120.0 degrees celsius

**Coating Material:**

Raychem: precoating 86 and adhesive s-1048

**Environmental Protection:**

Fluid resistant

**Main Body Inside Diameter:**

1.000 inches as supplied

**First Branch Inside Diameter:**

0.140 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

1.410 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.100 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.040 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

1.520 inches after unrestricted recovery

**Main Bodylength:**

3.640 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

45.0 after unrestricted recovery

**End Application:**

Propulsion section assembly, rmv; an/wld- (v) mine hunting system

**Features Provided:**

Adhesive coating

**Product Name:**

45 degree side-breakout transition (molded part)

**Special Features:**

Size 24

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Fluid resistant modified elastomer

**Material:**

Fluid resistant modified elastomer

**Style Designator:**

Transition-45 degrees

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500