

View Online at <https://aerobasegroup.com/nsn/5970-01-527-8814>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 120.0 degrees celsius

Coating Material:

Raychem: precoating 86 and adhesive s-1048

Environmental Protection:

Fluid resistant

Main Body Inside Diameter:

1.000 inches as supplied

First Branch Inside Diameter:

0.140 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.410 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.040 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.520 inches after unrestricted recovery

Main Bodylength:

3.640 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

End Application:

Propulsion section assembly, rmv; an/wld- (v) mine hunting system

Features Provided:

Adhesive coating

Product Name:

45 degree side-breakout transition (molded part)

Special Features:

Size 24

Flexibility:

Flexible

Color:

Black

Material:

Fluid resistant modified elastomer

Material:

Fluid resistant modified elastomer

Style Designator:

Transition-45 degrees

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500