

View Online at <https://aerobasegroup.com/nsn/5970-01-527-8818>

Reliability Indicator:

Not established

Temperature Rating:

-55.0 degrees celsius and 120.0 degrees celsius

Coating Material:

Raychem high-performance precoat no. 86 and adhesive s-1048

Environmental Protection:

Fluid resistant

Main Body Inside Diameter:

1.000 inches as supplied

First Branch Inside Diameter:

0.460 inches as supplied

Second Branch Inside Diameter:

0.460 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.700 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.100 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

End Application:

Propulsion section assembly, rmv; an/wld- (v) mine hunting sys

Features Provided:

Adhesive coating

Product Name:

Molded part: transition, y

Special Features:

Size 23

Flexibility:

Flexible

Color:

Black

Material:

Fluid resistant modified elastomer

Material:

Fluid resistant modified elastomer

Style Designator:

Transition-y

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500