

View Online at <https://aerobasegroup.com/nsn/5970-01-527-8833>

Reliability Indicator:

Not established

Temperature Rating:

-55.0 degrees celsius and 300.0 degrees celsius

Coating Material:

Raychem high-performance precoat adhesive no. S-1048

Environmental Protection:

Fluid resistant

Main Body Inside Diameter:

2.130 inches as supplied

First Branch Inside Diameter:

1.000 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.660 inches after unrestricted recovery

Main Body Wall Thickness:

0.180 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

3.760 inches after unrestricted recovery

Main Bodylength:

8.010 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Heat Shrinkage Rating In Percent:

50.0

End Application:

Propulsion sectionassy, rmv; an/wld- (v) mine hunting sys

Features Provided:

Adhesive coating

Product Name:

45 degree side-breakout transition (molded part)

Special Features:

Material is elastomer rt-1325

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Transition-45 degrees

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500