

View Online at <https://aerobasegroup.com/nsn/5970-01-527-9307>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 120.0 degrees celsius

Coating Material:

Raychem precoat no. 25, high-performance adhesive no. S-1048

Environmental Protection:

Fluid resistant

Main Body Inside Diameter:

1.000 inches as supplied

First Branch Inside Diameter:

0.460 inches as supplied

Second Branch Inside Diameter:

0.460 inches as supplied

Third Branch Inside Diameter:

0.460 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.980 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Third Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.690 inches after unrestricted recovery

Main Bodylength:

3.670 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

End Application:

Propulsion section assembly, rmv; an/wld- (v) mine hunting sys

Product Name:

Transition, one to three cables

Flexibility:

Flexible

Color:

Black

Material:

Fluid resistant modified elastomer

Material:

Fluid resistant modified elastomer

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500