

View Online at <https://aerobasegroup.com/nsn/5970-01-527-9334>

Reliability Indicator:

Not established

Temperature Rating:

-55.0 degrees celsius and 120.0 degrees celsius

Coating Material:

Raychem precoating no. 25, high-performance adhesive no. S-1048

Environmental Protection:

Fluid resistant

Main Body Inside Diameter:

0.700 inches as supplied

First Branch Inside Diameter:

0.310 inches as supplied

Second Branch Inside Diameter:

0.310 inches as supplied

Third Branch Inside Diameter:

0.310 inches as supplied

Fourth Branch Inside Diameter:

0.310 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

1.400 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.260 inches after unrestricted recovery

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

First Branch Wall Thickness:

0.040 inches after unrestricted recovery

Second Branch Wall Thickness:

0.040 inches after unrestricted recovery

Third Branch Wall Thickness:

0.040 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.040 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.420 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

15.0 after unrestricted recovery

Heat Shrinkage Rating In Percent:

50.0

End Application:

Propulsion section assembly, rmv; an/wld- (v) mine hunting sys

Features Provided:

Adhesive coating

Product Name:

Transition, 1 to 4 cables

Flexibility:

Flexible

Color:

Black

Material:

Fluid resistant modified elastomer

Material:

Fluid resistant modified elastomer

Style Designator:

Transition-1 to 4 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500