

View Online at <https://aerobasegroup.com/nsn/5970-01-528-1037>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Main Body Inside Diameter:**

1.400 inches as supplied

**First Branch Inside Diameter:**

0.400 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

1.400 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.110 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

0.750 inches after unrestricted recovery

**Main Bodylength:**

2.400 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

30.0 after unrestricted recovery

**End Application:**

Fuel/electronics assembly, rmv on an/wld- (v) mine hunting system

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Product Name:**

30 degrees side-breakout transition

**Special Features:**

Inside coated with adhesive

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-1304, raychem corp

**Material:**

Plastic, polyolefin, rt-1304, raychem corp

**Style Designator:**

Transition-45 degrees

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500