

View Online at <https://aerobasegroup.com/nsn/5970-01-530-3402>

**Reliability Indicator:**

Not established

**Temperature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

**Environmental Protection:**

Flame resistant and petroleum resistant and solvent resistant

**Main Body Wall Thickness:**

1.2 millimeters after unrestricted recovery

**Main Bodylength:**

42.0 millimeters as supplied

**Main Body Small End Inside Diameter:**

15.5 millimeters after unrestricted recovery

**Main Body Large End Inside Diameter:**

38.0 millimeters as supplied

**Distance From Bottom Of Shoulder To Large End Of Main Body:**

20.5 millimeters after unrestricted recovery

**Distance From Top Of Shoulder To Small End Of Main Body:**

19.5 millimeters after unrestricted recovery

**Heat Shrinkage Rating In Percent:**

50.0

**Markings:**

1 perforated score

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Product Name:**

Heat-shrinkable marker sleeve

**Special Features:**

Perforated score to produce multiple marker sleeves

**Flexibility:**

Flexible

**Color:**

Yellow

**Material:**

Plastic, polyolefin, mil-i-23053/5, class 1

**Material:**

Plastic cross-linked polyolefin

**Style Designator:**

Boot-straight

**Dielectric Material Voltage Rating Per Unit Thickness:**

500.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500