

View Online at <https://aerobasegroup.com/nsn/5970-01-530-3402>

Reliability Indicator:

Not established

Temperature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Flame resistant and petroleum resistant and solvent resistant

Main Body Wall Thickness:

1.2 millimeters after unrestricted recovery

Main Bodylength:

42.0 millimeters as supplied

Main Body Small End Inside Diameter:

15.5 millimeters after unrestricted recovery

Main Body Large End Inside Diameter:

38.0 millimeters as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

20.5 millimeters after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

19.5 millimeters after unrestricted recovery

Heat Shrinkage Rating In Percent:

50.0

Markings:

1 perforated score

Min. Tensile Strength (psi):

1500 pounds per square inch

Product Name:

Heat-shrinkable marker sleeve

Special Features:

Perforated score to produce multiple marker sleeves

Flexibility:

Flexible

Color:

Yellow

Material:

Plastic, polyolefin, mil-i-23053/5, class 1

Material:

Plastic cross-linked polyolefin

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

500.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500