NSN 5970-01-530-3422

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-530-3422
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Main Body Wall Thickness:
0.5 millimeters as supplied
Main Bodylength:
42.0 millimeters as supplied
Main Body Small End Inside Diameter:
9.5 millimeters after unrestricted recovery
Main Body Large End Inside Diameter:
18.0 millimeters as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
19.5 millimeters after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
20.0 millimeters after unrestricted recovery
Heat Shrinkage Rating In Percent:
50.0
Markings:
1 perforated score
Min. Tensile Strength (psi):
1500 pounds per square inch
Product Name:
Heat-shrinkable marker sleeve
Special Features:
Perforated score to produce multiple marker sleeves
Flexibility:
Flexible
Color:
Yellow
Material:
Plastic, polyolefin, mil-i-23053/5, class 1
Material:
Plastic cross-linked polyolefin
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
500.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5970-01-530-3422

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500