NSN 5970-01-530-3434

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-530-3434
Reliability Indicator:
Established
Main Body Inside Diameter:
0.240 inches after unrestricted recovery
First Branch Inside Diameter:
0.040 inches after unrestricted recovery
Second Branch Inside Diameter:
0.040 inches after unrestricted recovery
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
0.760 inches after unrestricted recovery
Main Body Wall Thickness:
0.060 inches after unrestricted recovery
First Branch Wall Thickness:
0.040 inches after unrestricted recovery
Second Branch Wall Thickness:
0.040 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
0.940 inches after unrestricted recovery
Angle Between Main Body And Second Branch Centerlines In Deg:
0.2 after unrestricted recovery
End Application:
Engine adapter
Markings:
382a0
Product Name:
Inavy: transition, y, mold
Flexibility:
Flexible
Color:
Any acceptable
Material:
Plastic, polyethylene
Material:
Plastic polyethylene
Style Designator:
Transition-y
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5970-01-530-3434

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500