

View Online at <https://aerobasegroup.com/nsn/5970-01-530-3617>

Reliability Indicator:

Not established

Environmental Protection:

Hydraulic fluid and jet fuel resistant and oil resistant and water resistant and hydraulic fluid and petroleum resistant and solvent resistant and any acceptable

Main Body Inside Diameter:

0.380 inches after unrestricted recovery

First Branch Inside Diameter:

0.270 inches after unrestricted recovery

Second Branch Inside Diameter:

0.270 inches after unrestricted recovery

Third Branch Inside Diameter:

0.270 inches after unrestricted recovery

Fourth Branch Inside Diameter:

0.270 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

1.940 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.770 inches after unrestricted recovery

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Third Branch Wall Thickness:

0.060 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.000 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

15.0 after unrestricted recovery

End Application:

Engine adapter

Markings:

382a0

Product Name:

Inavy: transition, y, mold

Special Features:

Fluid resistant; operating temperature -55 to +120 degrees c

Flexibility:

Flexible

Color:

Any acceptable

Material:

Plastic, polyethylene

Material:

Plastic polyethylene

Style Designator:

Transition-1 to 4 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500