

View Online at https://aerobasegroup.com/nsn/5970-01-533-6984

| Reliability Indicator: |
|---|
| Not established |
| Main Body Inside Diameter: |
| 1.060 inches as supplied |
| First Branch Inside Diameter: |
| 0.520 inches as supplied |
| Second Branch Inside Diameter: |
| 0.520 inches as supplied |
| Distance From Intersecting Centerline Of Main Body To End Of First Branch: |
| 1.530 inches after unrestricted recovery and 1.870 inches after unrestricted recovery |
| Main Body Wall Thickness: |
| 0.080 inches after unrestricted recovery and 0.120 inches after unrestricted recovery |
| First Branch Wall Thickness: |
| 0.048 inches after unrestricted recovery and 0.072 inches after unrestricted recovery |
| Second Branch Wall Thickness: |
| 0.048 inches after unrestricted recovery and 0.072 inches after unrestricted recovery |
| Distance From Edge Of Main Body To Intersecting Centerlines: |
| 1.350 inches after unrestricted recovery and 1.650 inches after unrestricted recovery |
| Angle Between Main Body And Second Branch Centerlines In Deg: |
| 22.5 after unrestricted recovery |
| End Application: |
| Cable assembly set |
| Features Provided: |
| Adhesive coating |
| Product Name: |
| Inavy): transition, 1 to 2 |
| Flexibility: |
| Fluid-resistant |
| Color: |
| Black |
| Material: |
| Rubber, synthetic |
| Material: |
| Rubber synthetic |
| Style Designator: |
| Transition-y |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5970-01-533-6984

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

