

View Online at <https://aerobasegroup.com/nsn/5970-01-533-9384>

Reliability Indicator:

Established

Tempurature Rating:

-55.0 degrees celsius

Main Body Inside Diameter:

2.190 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Second Branch Inside Diameter:

1.060 inches as supplied

Third Branch Inside Diameter:

1.060 inches as supplied

Fourth Branch Inside Diameter:

1.060 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

4.000 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.640 inches as supplied

Main Body Wall Thickness:

0.180 inches as supplied

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Second Branch Wall Thickness:

0.100 inches after unrestricted recovery

Third Branch Wall Thickness:

0.100 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.100 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

4.270 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

10.0 as supplied

Angle Between Main Body And Second Branch Centerlines In Deg:

10.0 as supplied

Markings:

Body marked wit cage and p/n

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Material, plastic elastomer, rt-1325, raychem corp; main body id after recovery 1.050 inches. Branches 1 through 4 id after recovery is 0.510 inches; main body and branches 1 through 4 wall thickness aftewr recovery is 0.100 inches

Flexibility:

Flexible

Color:

Black

Material:

Plastic

Material:

Plastic

Style Designator:

Transition-1 to 4 cables

Dielectric Material Voltage Rating Per Unit Thickness:

300.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500