

View Online at <https://aerobasegroup.com/nsn/5970-01-534-1795>

**Dielectric Withstanding Voltage In Volts:**

300.0

**Reliability Indicator:**

Established

**Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and mildew resistant and flame resistant and jet fuel resistant and hydraulic fluid and oil resistant

**Main Body Inside Diameter:**

1.060 inches as supplied

**First Branch Inside Diameter:**

0.520 inches as supplied

**Second Branch Inside Diameter:**

0.520 inches as supplied

**Third Branch Inside Diameter:**

0.520 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

1.980 inches as supplied

**Main Body Wall Thickness:**

0.100 inches as supplied

**First Branch Wall Thickness:**

0.060 inches as supplied

**Second Branch Wall Thickness:**

0.060 inches as supplied

**Third Branch Wall Thickness:**

0.060 inches as supplied

**Distance From Edge Of Main Body To Intersecting Centerlines:**

1.690 inches as supplied

**Main Bodylength:**

3.670 inches as supplied

**Angle Between Main Body And First Branch Centerlines In Deg:**

30.0 as supplied

**End Application:**

Insulation, sleeving

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Flexibility:**

Semirigid

**Color:**

Black

**Material:**

Plastic, polyolefin

**Material:**

Plastic polyolefin

**Style Designator:**

Transition-1 to 3 cables

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500