

View Online at <https://aerobasegroup.com/nsn/5970-01-534-1795>

Dielectric Withstanding Voltage In Volts:

300.0

Reliability Indicator:

Established

Tempurature Rating:

-55.0 degrees celsius and 225.0 degrees celsius

Environmental Protection:

Corrosion resistant and mildew resistant and flame resistant and jet fuel resistant and hydraulic fluid and oil resistant

Main Body Inside Diameter:

1.060 inches as supplied

First Branch Inside Diameter:

0.520 inches as supplied

Second Branch Inside Diameter:

0.520 inches as supplied

Third Branch Inside Diameter:

0.520 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.980 inches as supplied

Main Body Wall Thickness:

0.100 inches as supplied

First Branch Wall Thickness:

0.060 inches as supplied

Second Branch Wall Thickness:

0.060 inches as supplied

Third Branch Wall Thickness:

0.060 inches as supplied

Distance From Edge Of Main Body To Intersecting Centerlines:

1.690 inches as supplied

Main Bodylength:

3.670 inches as supplied

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 as supplied

End Application:

Insulation, sleeving

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500