Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-534-1942

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Flame resistant and mildew resistant
Main Body Inside Diameter:
0.780 inches as supplied
First Branch Inside Diameter:
0.520 inches as supplied
Second Branch Inside Diameter:
0.520 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
1.600 inches after unrestricted recovery
Main Body Wall Thickness:
0.040 inches after unrestricted recovery
First Branch Wall Thickness:
0.040 inches after unrestricted recovery
Second Branch Wall Thickness:
0.040 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
1.600 inches after unrestricted recovery
End Application:
Jet engine test instruments; cable asy, intercom
Markings:
No markings
Min. Tensile Strength (psi):
1500 pounds per square inch
Product Name:
(inavy): transition
Special Features:
Material: viton polymer blend
Flexibility:
Flexible
Color:
Black
Material:
Rubber, synthetic
Material:
Rubber synthetic
Style Designator:
Transition-y



Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500