NSN 5970-01-534-4279

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-534-4279

Reliability Indicator:

Not established

Main Body Inside Diameter:

1.000 inches after unrestricted recovery

First Branch Inside Diameter:

0.490 inches after unrestricted recovery

Second Branch Inside Diameter:

0.490 inches after unrestricted recovery

Third Branch Inside Diameter:

0.490 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

4.060 inches after unrestricted recovery

Main Body Wall Thickness:

0.180 inches after unrestricted recovery

First Branch Wall Thickness:

0.120 inches after unrestricted recovery

Second Branch Wall Thickness:

0.120 inches after unrestricted recovery

Third Branch Wall Thickness:

0.120 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.800 inches after unrestricted recovery

Main Bodylength:

7.560 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

End Application:

Cable assembly cas mx; cable assembly, int; cable assembly cass e-2c pse pccn: p0hfd0

Flexibility:

Flexible

Material:

Rubber, synthetic

Material:

Rubber synthetic

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5970-01-534-4279

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500