

View Online at https://aerobasegroup.com/nsn/5970-01-534-4303

Reliability Indicator:
Not established
Main Body Inside Diameter:
0.730 inches after unrestricted recovery
First Branch Inside Diameter:
0.380 inches after unrestricted recovery
Second Branch Inside Diameter:
0.380 inches after unrestricted recovery
Third Branch Inside Diameter:
0.380 inches after unrestricted recovery
Fourth Branch Inside Diameter:
0.380 inches after unrestricted recovery
Distance From Intersecting Centerline Of Main Body To End Of Second Branch:
2.830 inches after unrestricted recovery
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
2.570 inches after unrestricted recovery
Main Body Wall Thickness:
0.120 inches after unrestricted recovery
First Branch Wall Thickness:
0.070 inches after unrestricted recovery
Second Branch Wall Thickness:
0.070 inches after unrestricted recovery
Third Branch Wall Thickness:
0.070 inches after unrestricted recovery
Fourth Branch Wall Thickness:
0.070 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
2.950 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
45.0 after unrestricted recovery
Angle Between Main Body And Second Branch Centerlines In Deg:
15.0 after unrestricted recovery
End Application:
Cable assembly cas mx; cable assembly, int; cable assembly cass e-2c pse pccn: p0hfd0
Flexibility:
Flexible
Material:
Rubber, synthetic
Material:
Rubber synthetic
Style Designator:
Transition-1 to 4 cables

NSN 5970-01-534-4303

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500