NSN 5970-01-536-5730

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-536-5730

Reliability Indicator:

Established

Tempurature Rating:

-35.0 degrees celsius and 155.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and weather resistant

Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.040 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

1.810 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

1.020 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.420 inches as supplied

Main Body Large End Inside Diameter:

1.420 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

0.590 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

End Application:

Misc end item

Markings:

Mark w/152-100/184

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Specific matl is raychem rt-1323 w/coating slash no /180/184 (s-1030)

Flexibility:

Semiflexible

Height:

1.500 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Boot-90 degrees

NSN 5970-01-536-5730

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:			
N/a			
Unit	Of I	Vlea	asure:

Demilitarization:

No

Fiig:

A22500