NSN 5970-01-549-4569

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-549-4569

Reliability Indicator:

Not established

Tempurature Rating:

-75.0 degrees celsius and 150.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.400 inches as supplied

First Branch Inside Diameter:

0.600 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.620 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Main Bodylength:

2.500 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

End Application:

Cable assembly

Markings:

Nno marking

Min. Tensile Strength (psi):

1500 pounds per square inch

Product Name:

Transition

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Style Designator:

Transition-45 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-549-4569

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A22500