NSN 5970-01-552-0591

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-552-0591

| Reliability Indicator: |
|---|
| Established |
| Tempurature Rating: |
| -20.0 degrees celsius and 60.0 degrees celsius |
| Main Body Inside Diameter: |
| 0.520 inches as supplied |
| First Branch Inside Diameter: |
| 0.260 inches as supplied |
| Second Branch Inside Diameter: |
| 0.260 inches as supplied |
| Third Branch Inside Diameter: |
| 0.260 inches as supplied |
| Fourth Branch Inside Diameter: |
| 0.260 inches as supplied |
| Distance From Intersecting Centerline Of Main Body To End Of Second Branch: |
| 1.730 inches as supplied |
| Distance From Intersecting Centerline Of Main Body To End Of First Branch: |
| 1.730 inches as supplied |
| Main Body Wall Thickness: |
| 0.060 inches as supplied |
| First Branch Wall Thickness: |
| 0.040 inches as supplied |
| Second Branch Wall Thickness: |
| 0.040 inches as supplied |
| Third Branch Wall Thickness: |
| 0.040 inches as supplied |
| Fourth Branch Wall Thickness: |
| 0.040 inches as supplied |
| Distance From Edge Of Main Body To Intersecting Centerlines: |
| 1.510 inches as supplied |
| Angle Between Main Body And First Branch Centerlines In Deg: |
| 45.0 as supplied |
| Angle Between Main Body And Second Branch Centerlines In Deg: |
| 15.0 as supplied |
| End Application: |
| Aircraft, av8b |
| Markings: |
| No marking |
| Product Name: |
| Transition |
| Special Features: |
| Next higher assembly: cable assemblies; coating: adhesive; rt spec: rt-1304 |

NSN 5970-01-552-0591

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



| Flexibility: |
|--------------------------|
| Flexible |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin |
| Material: |
| Plastic polyolefin |
| Style Designator: |
| Transition-1 to 4 cables |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A22500