

View Online at <https://aerobasegroup.com/nsn/5970-01-577-4744>

**Dielectric Withstanding Voltage In Volts:**

600.0

**Reliability Indicator:**

Established

**Overall Length:**

Between 100.000 feet and 500.000 feet

**Tempurature Rating:**

-55.0 degrees celsius and 175.0 degrees celsius

**Expanded Inside Diameter:**

0.125 inches

**Recovered Inside Diameter:**

0.062 inches

**Recovered Wall Thickness:**

0.020 inches

**Heat Shrinkage Rating In Percent:**

50.0

**End Application:**

Helicopter systems

**Design Form:**

Full round

**Markings:**

Comes spooled; customer cuts to specific length needed

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Product Name:**

Flexible heat shrink sleeving

**Special Features:**

Flexible polyolefin marker sleeve for use with sumimark iii marking machine; 2: 1 shrink ratio; rohs compliant; meets sae-as81531 and ams-dtl-23053/5c, class 1 and class 3; recognized by ul subject 224 as 125deg c, 600v (vw-1) rated; general purpose and electrical insulation of light wire harness assemblies; comes spooled-actual length not known

**Flexibility:**

Flexible

**Color:**

Green

**Material:**

Plastic, polyolefin or plastic, polyolefin, mil-i-23053/5, class 1

**Material:**

Plastic polyolefin or plastic cross-linked polyolefin

**Style Designator:**

Shrinkable

**Supplementary Features:**

heat shrink temp is 90 degrees cel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500