NSN 5970-01-580-2165

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-580-2165

Main Body Inside Diameter:

0.3 millimeters after unrestricted recovery

First Branch Inside Diameter:

0.2 millimeters after unrestricted recovery

Second Branch Inside Diameter:

0.2 millimeters after unrestricted recovery

Third Branch Inside Diameter:

0.2 millimeters after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.9 millimeters after unrestricted recovery

Main Body Wall Thickness:

0.1 millimeters after unrestricted recovery

First Branch Wall Thickness:

0.0 millimeters after unrestricted recovery

Second Branch Wall Thickness:

0.0 millimeters after unrestricted recovery

Third Branch Wall Thickness:

0.0 millimeters after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.6 millimeters after unrestricted recovery

Main Bodylength:

3.6 millimeters after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A22500