

View Online at https://aerobasegroup.com/nsn/5970-01-588-6855

| Reli | iability Indicator: |
|------|--|
| Not | established |
| Mai | n Body Wall Thickness: |
| 0.05 | 50 inches after unrestricted recovery |
| Mai | n Bodylength: |
| 5.25 | 50 inches after unrestricted recovery |
| Mai | n Body Small End Inside Diameter: |
| 0.70 | 00 inches after unrestricted recovery |
| Mai | n Body Large End Inside Diameter: |
| 1.05 | 50 inches after unrestricted recovery |
| Dist | tance From Bottom Of Shoulder To Large End Of Main Body: |
| 4.47 | 70 inches after unrestricted recovery |
| Dist | tance From Top Of Shoulder To Small End Of Main Body: |
| 0.78 | 30 inches after unrestricted recovery |
| End | Application: |
| Cas | s/otps |
| Mar | kings: |
| Any | acceptable |
| Pro | duct Name: |
| Inav | /y: boot, heat shrink; cage: uni-boot |
| Spe | cial Features: |
| Fits | shield adapter entry sizes 06 through 09 |
| Flex | xibility: |
| Flex | kible |
| Col | or: |
| Blac | sk |
| Mat | erial: |
| Plas | stic |
| Mat | erial: |
| Plas | stic |
| Styl | le Designator: |
| Boo | t-straight |
| She | If Life: |
| N/a | |
| Uni | t Of Measure: |
| | |
| Den | nilitarization: |
| No | |
| Fiig | : |
| A22 | 500 |